

沖縄ハイポール標準寸法表（ボルト式継柱）

荷重 (kN)	呼び名	上 柱				下 柱					根入長 (m)	地 際 設 計 曲 げ モ ー メ ン ト (kN・m)	足 場 受 口 数	参 考 質 量 (kg)
		長 さ (m)	末 口 径 (cm)	元 口 径 (cm)	重 量 (kg)	長 さ (m)	末 口 径 (cm)	地 際 径 (cm)	元 口 径 (cm)	重 量 (kg)				
10	18-19-10	13	19	36.3	1,500	5	36.3	39.0	43.0	890	3.0	147.50	34	2,390
	19-19-10	13	19	36.3	1,500	6	36.3	40.3	44.3	1,090	3.0	157.50	37	2,590
	20-19-10	13	19	36.3	1,500	7	36.3	41.7	45.7	1,300	3.0	167.50	39	2,800
	21-19-10	13	19	36.3	1,500	8	36.3	43.0	47.0	1,520	3.0	177.50	41	3,020
	22-19-10	13	19	36.3	1,500	9	36.3	44.3	48.3	1,740	3.0	187.50	43	3,240
	23-19-10	13	19	36.3	1,500	10	36.3	45.7	49.7	1,970	3.0	197.50	45	3,470
	24-19-10	13	19	36.3	1,500	11	36.3	47.0	51.0	2,200	3.0	207.50	48	3,700
	25-19-10	13	19	36.3	1,500	12	36.3	48.3	52.3	2,440	3.0	217.50	50	3,940
15	18-22-15	13	22	39.3	1,870	5	39.3	42.0	46.0	1,010	3.0	221.25	36	2,880
	19-22-15	13	22	39.3	1,870	6	39.3	43.3	47.3	1,230	3.0	236.25	39	3,100
	20-22-15	13	22	39.3	1,870	7	39.3	44.7	48.7	1,460	3.0	251.25	41	3,330
	21-22-15	13	22	39.3	1,870	8	39.3	46.0	50.0	1,700	3.0	266.25	43	3,570
	22-22-15	13	22	39.3	1,870	9	39.3	47.3	51.3	1,950	3.0	281.25	45	3,820
	23-22-15	13	22	39.3	1,870	10	39.3	48.7	52.7	2,200	3.0	296.25	47	4,070
	24-22-15	13	22	39.3	1,870	11	39.3	50.0	54.0	2,460	3.0	311.25	50	4,330
	25-22-15	13	22	39.3	1,870	12	39.3	51.3	55.3	2,730	3.0	326.25	52	4,600
	26-22-15	13	22	39.3	1,870	13	39.3	52.7	56.7	3,000	3.0	341.25	54	4,870
	27-22-15	13	22	39.3	1,870	14	39.3	54.0	58.0	3,280	3.0	356.25	56	5,150
18	18-26-18	10	26	39.3	1,610	8	39.3	46.0	50.0	1,800	3.0	265.50	37	3,410
	19-26-18	10	26	39.3	1,610	9	39.3	47.3	51.3	2,060	3.0	283.50	39	3,670
	20-26-18	10	26	39.3	1,610	10	39.3	48.7	52.7	2,330	3.0	301.50	41	3,940
	21-26-18	10	26	39.3	1,610	11	39.3	50.0	54.0	2,600	3.0	319.50	44	4,210
	22-26-18	10	26	39.3	1,610	12	39.3	51.3	55.3	2,880	3.0	337.50	46	4,490
20	18-26-20	10	26	39.3	1,620	8	39.3	46.0	50.0	1,820	3.0	295.00	37	3,440
	19-26-20	10	26	39.3	1,620	9	39.3	47.3	51.3	2,090	3.0	315.00	39	3,710
	20-26-20	10	26	39.3	1,620	10	39.3	48.7	52.7	2,360	3.0	335.00	41	3,980
	21-26-20	10	26	39.3	1,620	11	39.3	50.0	54.0	2,640	3.0	355.00	44	4,260
	22-26-20	10	26	39.3	1,620	12	39.3	51.3	55.3	2,930	3.0	375.00	46	4,550

※荷重は、JIS A 5373 プレキャストプレストレストコンクリート製品 附属書Aによる。

※根入長は、標準を示しています。設計においては安全率2.0以上を確保して下さい。

※部品取付図（姿図）については弊社へお問い合わせ下さい。